

4CH STI SERIES



STI Series DVR accepts ANALOG / 960H / HD-TVI / IP CAMERA



- REAL-TIME Live / 1/16fps to REAL-TIME Frame Rate
- H.264 / Dual Streaming
- RS-485 for PTZ control
- Free DDNS Support / EZVIZ Cloud P2P
- Manufactured by Hikvision



REAR PANEL

FEATURES

- Connectable to HD-TVI and analog cameras
- Connectable to the Coaxitron camera with long transmission distance
- Connectable to network cameras
- Simultaneous HDMI and VGA outputs at up to 1920x1080P resolution
- New GUI and support starting record with one key
- Redundant recording and holiday recording
- Instant playback for assigned camera during multi-channel live view mode
- Support up to 4-ch synchronous playback at 1080P resolution; and reverse playback for multi-camera
- Smart playback to go through less effective information
- Manual video quality diagnostics
- Customization of tags, searching & playing back by tags
- Locking and unlocking record files
- Support HDD quota and group management; different capacity can be assigned to different cameras under quota mode
- Provide up to 1 SATA interfaces for recording
- Up to 1 self-adaptive 10M/100M/1000M network interface
- Support access by EZVIZ Cloud P2P
- Support Hikvision DDNS (Dynamic Domain Name System)
- Network detection function.

TVST STI704	
VIDEO/AUDIO INPUT	
Video Compression	H.264
Analog & HD-TVI Video Input	4Ch / BNC Interface (1.0Vp-p, 75Ω)
Supported Camera Types	720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS
IP Video Input	1Ch Up to 2.0MP Resolution
Audio Compression	G.711u
Audio Input/Two-way Audio In	1-ch, RCA (2.0 Vp-p, 1 KΩ)
VIDEO/AUDIO OUTPUT	
HDMI/VGA Output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
Encoding Resolution	Main stream: 1080P(non-real-time) / 720P / VGA / WD1 / 4CIF / CIF Sub-stream: WD1(non-real-time) / 4CIF(non-real-time) / CIF / QCIF / QVGA
Frame Rate	Main stream: 1/16 fps ~ Real time frame rate Sub-stream: 1/16 fps ~ Real time frame rate
Video Bitrate	32 Kbps-6 Mbps
Audio Output	1-ch, RCA (Linear, 1KΩ)
Audio Bitrate	64 Kbps
Dual Stream	Support
Stream Type	Video, Video & Audio
Synchronous Playback	4Ch
Playback Resolution	1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF
NETWORK MANAGEMENT	
Remote Connections	128
Network Protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
HARD DISK	
SATA	1 SATA Interface
Capacity	Up to 6TB capacity for each disk
EXTERNAL INTERFACE	
Network Interface	1; 10M / 100M self-adaptive Ethernet interface
Serial Interface	1; standard RS-485 serial interface, half-duplex
USB Port	2 × USB 2.0
GENERAL	
Power Supply	12V DC
Consumption (w/o hard disks)	≤ 15W
Working Temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)
Working Humidity	10%~90%
Chassis	1U chassis
Dimensions (W x D x H)	315 × 242 × 45mm (12.4 × 9.5 × 1.8 inch)

SMART PHONE COMPATIBLE



Guarding Expert



HDD INSTALLATION AVAILABLE UPON REQUEST
IR REMOTE & MOUSE INCLUDED